

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **IDPFFWH-W**

GRID-IT | GRID-IT RANGE | Rocker Switch Modules 20AX Double Pole Rocker Module + Printed Legend

Item Image	Wiring	Dimensions
NO IMAGE	BS EN 60669 20AX 250V~ Double Pole L OUT N Live Noutral To To Load Load	Hamilton GRID-IT GDP 20AX Double Pole Rocker Module
Primary Range	GRID-IT	
Insert Type	20AX Double Pole Rocker Module + Printed Legend	
Insert Colour	White Fridge Freezer/White	
EAN13 Barcode	5017504070441	
Commodity Code	85363030	
Luckins TSI	407290073	
Dimensions(Nominal)	Module: Height = Width = Depth =	
Weight	43 GR	
Switched Poles	Double	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5x1mm²	
Terminal Capacity 2	4x1.5mm <sup>2</sup>	
Terminal Capacity 3	2x2.5mm <sup>2</sup>	
Terminal Capacity 4	lx4mm² Multi-strand	
Terminal Capacity 5	lx6mm²	
Earth Terminal Capacity 1	6x1mm <sup>2</sup>	
Earth Terminal Capacity 2	5x1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	3x2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	2x4mm² Multi-strand	
Earth Terminal Capacity 5	lx6mm²	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	



.

## **IDPFFWH-W**

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

Standard/Approval	BS EN 60669-1	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 18 August 2021 12:19 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84		Listed in *Trimble product selector CRT.No. TMB1238