

590.EM2015**SWITCH DISCONNECTOR**

20A 3P+N IP66/IP69 110x150x87mm
Y1 IK09 EMERGENCY YELLOW/RED
GW 650°C



EN IEC 60947-1 (2021)

EN IEC 60947-3 (2021)

Low voltage direct. 2014/35/EU

Commercial Series**ISOLATORS-TP Series****Synthetical description****SWITCH DISCONNECTOR****Type****EMERGENCY****■ TECHNICAL CHARACTERISTICS**

Rated current	20A
Poles	3P+N
Switch size	Y1
Rated voltage	690V
Rated insulation voltage (Ui)	690VAC
Rated impulse voltage (Uimp)	4kV
Thermal current (Ithe)	20A
Current (Ie) in AC21A (415V)	20A
Current (Ie) in AC21A (500V)	20A
Current (Ie) in AC21A (690V)	20A
Current (Ie) in AC22A (415V)	20A
Current (Ie) in AC22A (500V)	20A
Current (Ie) in AC22A (690V)	20A
Current (Ie) in AC23A (415V)	20A
Current (Ie) in AC23A (500V)	20A
Current (Ie) in AC23A (690V)	20A
Current (Ie) in AC3 (415V)	18A
Current (Ie) in AC3 (690V)	12A
Current (Ie) in DC22A (250V)	25A
Current (Ie) in DC22A (600V)	10A
Power AC23A (415V)	9kW
Short-time current	400A Icw(1s)
Conditional short circuit cur.	10kAeff
Associate fuse - type gG	20A
Terminals - Flexible wires	1.5-10mm ²
Terminals - Rigid wires	1.5-16mm ²

■ PHYSICAL CHARACTERISTICS

Material	ENGINEERING PLASTIC
Protection degree IP	IP66/IP69
Installation temperature	-25°C/+60°C
Colour	YELLOW/RED
GLOW WIRE	GW 650°C
Protection degree IK	IK09

■ DIMENSIONAL CHARACTERISTICS

Dimensions	110x150x87mm
------------	--------------

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Handle padlockable in OFF position only (3 padlocks)
Catalogue notes	Equipped with door interlock
Catalogue notes	With late break and early make neutral pole
Catalogue notes	Blank side with drilling point marks on top side base
Catalogue notes	Break-through cable entries on bottom side base
Catalogue notes	Reversible base