



Main

Range	Exclusive
Product or component type	Push-button dimmer
Quantity per set	Set of 1
Device presentation	Complete product
Load type	Incandescent lamp Dimmable fluocompact lamp: 250 W
Colour tint	White matt

Complementary

Device mounting	Wall mounted
Dimmer application	Inductive load Resistive load
[Ue] rated operational voltage	230 V AC 50 Hz
Number of gangs	2 gangs
Connections - terminals	Screw terminals
Fixing mode	By screws M3.5 x 30 mm
Material	Urea (carbamide)
Height	86 mm
Width	86 mm
Depth	17 mm

Environment

Standards	BS EN 60669-2-1
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.700 cm
Package 1 Width	9.200 cm
Package 1 Length	9.100 cm
Package 1 Weight	171.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Height	21.000 cm
Package 2 Width	48.000 cm
Package 2 Length	50.000 cm
Package 2 Weight	17.790 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	1600
Package 3 Height	100.500 cm
Package 3 Width	120.000 cm
Package 3 Length	100.000 cm
Package 3 Weight	304.640 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins