

DATA SHEET

PHOENIX


Phoenix LED 65W 5Ft High Output M3 850

IP20 Traditional LED Batten Fitting
Full Range of Attachments
Direct Replacement for Traditional Battens



GENERAL INFORMATION	
Product Code	NPH65/LED/M3/850
Product Range	Phoenix
Product Category	Surface Mount
Fixing Method	Surface
IP Rating	20
IK Rating	N/A
Warranty	5 Years Unlimited Hours
DIMENSION/WEIGHT	
Dimensions (L x W x H) (mm)	L=undefined, W=61, H=64
Cut-out Size (mm)	N/A
Product Weight (Kg)	3.07
CONSTRUCTION	
Body Material	Steel Body
Body Colour	White
Optical Material	PC
Optical Finish	Opal
Termination	4x2x2.5mm sq. Push In Terminal
Driver - Integral or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	8350
Power Consumption (W)	65
Efficacy (l.lm/c.W)	127
Operating Temp. (Min/Max)	0°C - 25 °C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	5000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80:B10 50000
SDCM	<5
ELECTRICAL INPUT	
Voltage (V)	220-240V AC
Operating Frequency	50
In Rush	<28A
Drivers per MCB*	B10=9 B16=15
Class	Class 1
Power Factor	>0.95
Cable Entry	On Ends / back
ELECTRICAL OUTPUT	
Forward Current (mA)	1440
Forward Voltage (Vf)	41
EMERGENCY DATA	
Mode of Operation	Maintained
Battery Duration	3 Hours
Battery Type	3 Hours
Battery Specification	6V 1.8Ah
Ballast Lumen Factor (BLF)	3.40%
DIMMING	
DALI	Yes
OTHER	N/A
Switch Dim	Yes
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	yes
Certificate of Conformity	yes
Accreditations	N/A
BARCODE	
EAN Number	5055825967019



* GUIDE ONLY