## **X**nightsbridge

## **DATASHEET**



## **FP8900PC**

Flat Plate 115/230V dual voltage shaver socket - polished chrome with black insert

www.mlaccessories.co.uk

FINISH INSERT COLOUR Black  DIMENSIONS (MM) Height - 147.5 Width - 87.5 Projection - 2.5  MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION IP41 INPUT VOLTAGE 1094 SECONDARY VOLTAGE 115/230V EARTH TERMINAL Yes LOAD/MAX. LOAD 20VA TERMINAL CAPACITY WARRANTY 15year(s)	MLA PART CODE	FP8900PC
FINISH INSERT COLOUR Black  DIMENSIONS (MM) Height - 147.5 Width - 87.5 Projection - 2.5  MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION IP41 INPUT VOLTAGE 1094 SECONDARY VOLTAGE 115/230V EARTH TERMINAL Yes LOAD/MAX. LOAD 20VA TERMINAL CAPACITY WARRANTY 15year(s)	DESCRIPTION	
INSERT COLOUR  Black  Height - 147.5 Width - 87.5 Projection - 2.5  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  IP41  INPUT VOLTAGE  SECONDARY VOLTAGE  EARTH TERMINAL  LOAD/MAX. LOAD  TERMINAL CAPACITY  WARRANTY  Black  Height - 147.5 Width - 87.5 Projection - 2.5  MINIMUM MOUNTING BOX DEPTH  47mm  Construction - Premium grade steel  IP41  IP41  IP41  IP41  Yes  115/230V  2 x 2.5mm² or 1 x 4.0mm²  Height - 147.5 Vidth - 87.5 Projection - 2.5  IP41  I	NET WEIGHT (KG)	0.63
DIMENSIONS (MM)Height - 147.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH47mmCONSTRUCTIONConstruction - Premium grade steelIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYesLOAD/MAX. LOAD20VATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²WARRANTY15year(s)	FINISH	Polished Chrome
DIMENSIONS (MM)  Width - 87.5 Projection - 2.5  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  Construction - Premium grade steel  IP RATING  IP41  INPUT VOLTAGE  SECONDARY VOLTAGE  EARTH TERMINAL  Yes  LOAD/MAX. LOAD  TERMINAL CAPACITY  WARRANTY  WARRANTY  WIdth - 87.5 Projection - 2.5  A7mm  47mm  Construction - Premium grade steel  IP41  230V 50Hz  230V 50Hz  230V 50Hz  230V 50Hz  115/230V  2 × 2.5mm² or 1 × 4.0mm²  15year(s)	INSERT COLOUR	Black
CONSTRUCTION         Construction - Premium grade steel           IP RATING         IP41           INPUT VOLTAGE         230V 50Hz           SECONDARY VOLTAGE         115/230V           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         20VA           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           WARRANTY         15year(s)	DIMENSIONS (MM)	Width - 87.5
IP RATING         IP41           INPUT VOLTAGE         230V 50Hz           SECONDARY VOLTAGE         115/230V           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         20VA           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           WARRANTY         15year(s)	MINIMUM MOUNTING BOX DEPTH	47mm
INPUT VOLTAGE         230V 50Hz           SECONDARY VOLTAGE         115/230V           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         20VA           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           WARRANTY         15year(s)	CONSTRUCTION	Construction - Premium grade steel
SECONDARY VOLTAGE         115/230V           EARTH TERMINAL         Yes           LOAD/MAX. LOAD         20VA           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           WARRANTY         15year(s)	IP RATING	IP41
EARTH TERMINAL         Yes           LOAD/MAX. LOAD         20VA           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           WARRANTY         15year(s)	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD         20VA           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           WARRANTY         15year(s)	SECONDARY VOLTAGE	115/230V
TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           WARRANTY         15year(s)	EARTH TERMINAL	Yes
WARRANTY 15year(s)	LOAD/MAX. LOAD	20VA
, , ,	TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
NAMES OF THE PROPERTY OF THE P	WARRANTY	15year(s)
MANUFACTURED IN ACCORDANCE WITH BS EN 61558-2-5	MANUFACTURED IN ACCORDANCE WITH	BS EN 61558-2-5
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
<b>EAN</b> 5055832919049	EAN	5055832919049

Date Created: 04/04/2022 10:40





