



Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Switched socket
Device presentation	Complete product
Outlet standard	British
Colour tint	Matt white
Quantity per set	Set of 5
Type of packing	Carton

Complementary

Switch function	2-pole
Rated current	13 A at 250 V AC 50 Hz
Actuator	Key
Number of gangs	2 gangs
Pilot light	without LED
Fixing mode	By screws
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of installation	Indoor
Depth	43.8 mm
Width	148.5 mm
Height	87 mm

Environment

Standards	BS 1363-2
IP degree of protection	IP20

Packing Units

Package 1 Height	44.000 mm
Package 1 width	87.000 mm
Package 1 Length	149.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------