



PVC Conduit

Specifications and Dimensions

Available in a diameter range of 16-63mm and lengths of 10-30m

- Material: Thermoplastic resin with polyvinyl chloride (PVC)
- Temperature range: -15°C to +70°C (Static), -5°C to +60°C (Moving)
- Ingress protection: IP65
- Manufactured to BS EN 61386 & UL 1696

Part No	Size	Colour	Int. ø	Ext. ø
ERS16PVC10MB	16mm x 10m	Black	12mm	16.2mm
ERS16PVC30MB	16mm x 30m	Black	12mm	16.2mm
ERS20PVC10MB	20mm x 10m	Black	16mm	20.2mm
ERS20PVC30MB	20mm x 30m	Black	16mm	20.2mm
ERS25PVC10MB	25mm x 10m	Black	22mm	26.3mm
ERS25PVC30MB	25mm x 30m	Black	22mm	26.3mm
ERS32PVC10MB	32mm x 10m	Black	28mm	33.0mm
ERS32PVC30MB	32mm x 30m	Black	28mm	33.0mm
ERS40PVC10MB	40mm x 10m	Black	35mm	40.2mm
ERS40PVC30MB	40mm x 30m	Black	35mm	40.2mm
ERS50PVC10MB	50mm x 10m	Black	40mm	45.3mm
ERS50PVC30MB	50mm x 30m	Black	40mm	45.3mm
ERS63PVC10MB	63mm x 10m	Black	50mm	56.0mm
ERS63PVC30MB	63mm x 30m	Black	50mm	56.0mm

For any further comments or assistance please contact:

eris-eu.com