

SLB2300

2300W PIR Light Controller – Black



Features & Benefits

- Pan and tilt feature
- Light ON times adjustable
- LUX (light level) adjustment – Day to Night
- Manual ON/OFF switching override
- IP55 weatherproof rating
- Simple and quick to fit terminal block connectors
- Corner mounting bracket available – SLBCB (Sold Separately)

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class I
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP55
Setting Type	Dial
Max Mounting Height (Mtr)	2.5
Motion Detection (Mtr)	12
Detection Angle	180°

Data sheet

SLB2300

Light / PIR Lighting Controllers

Pan & Tilt Adjustment	90° Left/Right From Centre, Tilt 15° (Up), 60° (Down)
Mounting Hole Centres (mm)	50
Standby Consumption	<1W
Number of Channels	1
Switch rating	250W LED, 500W Fluorescent, 2300W Halogen
ON Time Adjustment	5 Seconds to 15 Minutes. User Adjustable
Lux Level	5 to 1000
Detection Range (Mtr)	12
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Yes (Up to 4 In Parallel)
Cable Entry(s)	Back Entry, Bottom Entry

General

Weight (g)	193
Height (mm)	95
Width (mm)	78
Depth (mm)	141
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483013205
Guarantee Period	3 Years

Line Diagrams

