60894 Revelo Shaver Cabinet Mirror

FEATURES

- 2 years warranty
- Mirrored glass & matt silver finish
- Constructed from glass & steel
- Suitable for bathroom zone 1 & 2 and used in conjunction with a 30MA RCD
- Energy efficient product
- Supplied with IR switch
- · Built in dual shaver socket
- Includes 2 shelves
- IP44

SPEC DATA

| Product Wattage: | 7W |
|--|---|
| Product Lumen: | 170 |
| Lumen/W: | 24 |
| Kelvin: | 6500K |
| Energy Rating: | E |
| SDCM: | 4 |
| CRI: | 80 |
| Dimmable: | Ν |
| Lifetime (Hours): | 50000 |
| Beam Angle: | 120° |
| Power Factor: | 0.82 |
| Driver Type: | Constant Current 160mA |
| = | |
| Inrush Current at Start Up: | 5A |
| | 5A 24V |
| Inrush Current at Start Up: | •••• |
| Inrush Current at Start Up: Driver Output Voltage: | 24V |
| Inrush Current at Start Up: Driver Output Voltage: Shaver: | 24V 115V - 240V dual socket |
| Inrush Current at Start Up: Driver Output Voltage: Shaver: Product Voltage: | 24V 115V - 240V dual socket 220-240V |
| Inrush Current at Start Up: Driver Output Voltage: Shaver: Product Voltage: Hertz: | 24V 115V - 240V dual socket 220-240V 50/60 |
| Inrush Current at Start Up: Driver Output Voltage: Shaver: Product Voltage: Hertz: Surge Protection (KV): | 24V 115V - 240V dual socket 220-240V 50/60 2 |
| Inrush Current at Start Up: Driver Output Voltage: Shaver: Product Voltage: Hertz: Surge Protection (KV): Operating Temp.: | 24V 115V - 240V dual socket 220-240V 50/60 2 -20 to 45 Degree |
| Inrush Current at Start Up: Driver Output Voltage: Shaver: Product Voltage: Hertz: Surge Protection (KV): Operating Temp.: Product Weight (KG): | 24V 115V - 240V dual socket 220-240V 50/60 2 -20 to 45 Degree 13.55 |



