

Technical Specification



Product Code: VPSC570BK

Description: 13A Ingot 2 Gang Switched Socket Outlet With Single 2.1A USB Outlet





General Information

Dimensions
Dimensions With Gasket
Plate Design & Finish
Insert & Gasket Colour
Materials

Maximum Voltage Load Rating **Plate Fixing Centres Terminal Size Terminal Torque**

146mm (W) x 88mm (H) x 8mm (D)
149mm (W) x 91mm (H) x 9mm (D)
Victorian Satin Chrome
Black
Front Plate: Stainless Steel
Housing: Nylon
Terminals: Brass
Contacts: Silver "on-lay" Copper / Brass
PCB: Mixed Components
250V~ 50Hz
13A
120.6mm
5mmø
1.2Nm
3 x 2.5mm ² or 2 x 4mm ²
Yes
Yes
5V DC, 2.1A
1
USB Type "A"
2mA
USB 5V 2.1A
IP20
25mm Minimum
Screw
-5°C to +40°C
10 Years, 1 Year Electronics

Insert: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

1	
Terminal Capacity	3 x 2.5mm ² or 2 x 4mm ²
Single Pole	Yes
Twin Earth Terminals	Yes
USB Charging Output Total	5V DC, 2.1A
Number Of USB Outputs	1
USB Type	USB Туре "А"
USB Standby Current	2mA
Product Markings	USB 5V 2.1A
Ingress Protection	IP20
Back Box Depth	25mm Minimum
Termination Type	Screw
Operational Temperature	-5°C to +40°C
Warranty	10 Years, 1 Year Electronics
Standards	BS 1363-2: 2016 +A1: 2018 BS EN 62368-1: 2014, BS EN 62680-1-1: 2015
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

CE

Page Errors & Omiss

cification is sub