



Galvanised Steel Conduit

Specifications and Dimensions

Available in a diameter range of 16-50mm and lengths of 10-50m

- Material: Galvanised Steel
- Temperature range: -50°C to +300°C
- Ingress protection: IP40
- Manufactured to BS EN 61386

Part No	Size	Int. ø	Ext. ø	Bending Radius
ERS16GALV10M	16mm x 10m	13mm	16mm	33mm
ERS16GALV30M	16mm x 30m	13mm	16mm	33mm
ERS16GALV50M	16mm x 50m	13mm	16mm	33mm
ERS20GALV10M	20mm x 10m	17mm	20.5mm	38mm
ERS20GALV30M	20mm x 30m	17mm	20.5mm	38mm
ERS20GALV50M	20mm x 50m	17mm	20.5mm	38mm
ERS25GALV10M	25mm x 10m	21mm	25mm	45mm
ERS25GALV30M	25mm x 30m	21mm	25mm	45mm
ERS25GALV50M	25mm x 50m	21mm	25mm	45mm
ERS32GALV10M	32mm x 10m	28.5mm	32mm	55mm
ERS32GALV30M	32mm x 30m	28.5mm	32mm	55mm
ERS32GALV50M	32mm x 50m	28.5mm	32mm	55mm
ERS50GALV10M	50mm x 10m	48.5mm	53mm	110mm
ERS50GALV20M	50mm x 20m	48.5mm	53mm	110mm

For any further comments or assistance please contact:

eris-eu.com