



PVC Covered Galvanised Steel Conduit

Specifications and Dimensions

Available in a diameter range of 16-50mm and lengths of 10-50m

- Material: Galvanised Steel Core with PVC (Polyvinyl Chloride) Jacket
- Temperature range: -20°C to +70°C
- Ingress protection: IP54
- Manufactured to BS EN 61386

Part No	Size	Int. ø	Ext. ø	Bending Radius
ERS16GPVC10M	16mm x 10m	13mm	17mm	50mm
ERS16GPVC30M	16mm x 30m	13mm	17mm	50mm
ERS16GPVC50M	16mm x 50m	13mm	17mm	50mm
ERS20GPVC10M	20mm x 10m	17mm	21.5mm	65mm
ERS20GPVC30M	20mm x 30m	17mm	21.5mm	65mm
ERS20GPVC50M	20mm x 50m	17mm	21.5mm	65mm
ERS25GPVC10M	25mm x 10m	21mm	26mm	75mm
ERS25GPVC30M	25mm x 30m	21mm	26mm	75mm
ERS25GPVC50M	25mm x 50m	21mm	26mm	75mm
ERS32GPVC10M	32mm x 10m	28.5mm	34mm	100mm
ERS32GPVC30M	32mm x 30m	28.5mm	34mm	100mm
ERS32GPVC50M	32mm x 50m	28.5mm	34mm	100mm
ERS50GPVC10M	50mm x 10m	48.5mm	55mm	175mm
ERS50GPVC20M	50mm x 20m	48.5mm	55mm	175mm

For any further comments or assistance please contact:

eris-eu.com