



### Main

Range	Easy9
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Number of 18 mm modules per row	2
Provided equipment	earth/neutral terminal block busbar

### Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	2
Number of horizontal rows	1
Number of ways	2 ways
Enclosure material	Metal
Type of front cover	Plain
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Type of rail	DIN
Cable entry	Knock-out
Cable cross section	1...25 mm <sup>2</sup> incoming
Comb busbar and distribution block compatibility	YES
Net weight	3.499 kg
Height	276.8 mm
Width	212.8 mm
Depth	119.55 mm
Colour	White (RAL 9003)
Product compatibility	Easy9 RCBO

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Easy9 switch  
Easy9 SPD  
Easy9 RCCB  
Easy9 MCB

---

## Environment

Standards	BS EN 61439-3 BS 7671:amendment 3
IP degree of protection	IPxx D (on top) IP3x (with cover)
IK degree of protection	IK05
Overvoltage category	II

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------