



Main

Range	Easy9
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Number of 18 mm modules per row	6
Provided equipment	earth/neutral terminal block busbar

Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	6
Number of horizontal rows	1
Number of ways	6 ways
Enclosure material	Metal
Type of front cover	Plain
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Type of rail	DIN
Cable entry	Knock-out
Cable cross section	1...25 mm ² incoming
Comb busbar and distribution block compatibility	YES
Net weight	4.295 kg
Height	276.8 mm
Width	284.8 mm
Depth	119.55 mm
Colour	White (RAL 9003)
Product compatibility	Easy9 RCCB

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Easy9 MCB
Easy9 switch
Easy9 SPD
Easy9 RCBO

Environment

Standards	BS EN 61439-3 BS 7671:amendment 3
IP degree of protection	IPxx D (on top) IP3x (with cover)
IK degree of protection	IK05
Overvoltage category	II

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------