



Main

Range	Easy9
Product or component type	Consumer unit equipped
Provided equipment	1 x 6 A miniature circuit breaker (MCB) 1 x 16 A miniature circuit breaker (MCB) 1 x 63 A RCCB
Product compatibility	Easy9 RCBO Easy9 SPD Easy9 switch Easy9 RCCB Easy9 MCB
Number of 18 mm modules per row	2

Complementary

Enclosure type	Metal enclosure
Enclosure mounting	Surface
Type of front cover	Plain
Total number of 18 mm modules	2
Number of horizontal rows	1
Number of ways	2 ways
Network frequency	50 Hz
Type of rail	DIN
Cable entry	Knock-out
Cable cross section	1...25 mm ²
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Enclosure material	Metal
Height	276.8 mm
Width	212.8 mm

Depth	119.55 mm
Colour	White (RAL 9003)
Net weight	3.899 kg

Environment

Standards	BS EN 61439-3 BS 7671:amendment 3
IP degree of protection	IPxx D (on top) IP3x (with cover)
IK degree of protection	IK05
Overvoltage category	II

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------