# **X**nightsbridge


### **DATASHEET**



### **BL12LED**

#### 230V IP54 12W IP54 LED Bulkhead 4000K

www.mlaccessories.co.uk



MLA PART CODE	BL12LED
DESCRIPTION	230V IP54 12W IP54 LED Bulkhead 4000K
NET WEIGHT (KG)	0.72
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 305 Projection - 84
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP54
WATTAGE (W)	12
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1000
LUMENS LIGHT SOURCE ONLY (LM)	1240
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	77.4
CIRCUIT WATTAGE (W)	13.8
ССТ	4000K
LIGHT COLOUR	Cool White
RUNNING CURRENT (A)	0.063
DISPLACEMENT FACTOR	>0.7
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	110
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C





## **X**nightsbridge

INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current  MAX. OUTPUT - 12W  OUTPUT VOLTAGE - 27-42V  OUTPUT CURRENT - 350mA  POWER FACTOR - 0.9  EFFICIENCY FULL LOAD - 90  ISOLATION - SELV  AMBIENT TEMPERATURE (Ta)20 ~ 50°C  CASE TEMPERATURE (Tc) - 80°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832934608

Date Created: 22/04/2022 13:11





