

LED Panel 600

- Energy savings up to 60% when replacing 4x18W T8 luminaires
- Luminaire efficacy: Up to 100 Lumen/Watt
- Suitable for 25mm and 15mm T-bar ceilings
- Frame colour: White
- Standard non dimmable driver included
- Colour temperature: 3000K, 4000K and 6000K options
- Colour rendering index: >80
- Rated Life (L70): 50,000 hours
- Options available:
 - Dimmable driver 1-10v & DALI:
LXLPF2-30D-48
 - Dimmable driver Touch (Push) and DALI:
LXLPF2-900-DTD
 - Emergency 3 hour remote pack:
LXLPF2-60-EM3
 - 600x600mm Surface mounting frame:
LXPAN66SMB
 - Wire suspension kit:
LXPAN663SCK
 - Recessed fixing clips x4 pack:
LXPAN66RFC (x1 pack required)



5 YEAR
WARRANTY

LED

IP20

SAVE UP TO **60%**
ON ENERGY

L1A BUILDING REGULATIONS COMPLIANT

L2B BUILDING REGULATIONS COMPLIANT

Part No.	Wattage	Measurement L x W x H	Lumen Output	IP Rating	Colour Temperature
LXPAN28LED63NW2	28W	595 x 295 x 10.5mm	2240Lm	IP20	4000K
LXPAN28LED63CW2	28W	595 x 295 x 10.5mm	2240Lm	IP20	6000K
LXPAN30LED66WW2	30W	595 x 595 x 10.5mm	3000Lm	IP20	3000K
LXPAN30LED66NW2	30W	595 x 595 x 10.5mm	3000Lm	IP20	4000K
LXPAN30LED66CW2	30W	595 x 595 x 10.5mm	3000Lm	IP20	6000K



Email sales@luxna.co.uk



Web luxna-lighting.com