

Product Code: CL770

Luckinslive 402391728

Description: 13A 2 Gang Switched Socket Outlet With Single 2.1A USB Outlet



General Information

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Metal Clad		
Colour	Grey		
Materials	Front Plate & Mounting Box:	Electrophoretically Coated Steel	Insert & Rocker Switch: Urea
	Housing:	Nylon	Terminals: Brass
	Terminal Screws:	Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars:	Formed Pressed Brass	PCB: Mixed Components
	Earth Strap:	Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
USB Output Type	USB Type 'A'		
USB Number Of Outputs	1	USB Charging Total Load (A)	2.1
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Single Pole Switched	Yes		
Twin Earth Terminals	Yes		
Product Marking	USB 5V 2.1A		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	7 x Ø20	Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Rear (mm)	None
Back Box Knockouts - Bottom (mm)	2 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20	Warranty - Electronics (Years)	2

Standards BS 1363-2: 2016 +A1: 2018, BS EN IEC 62368-1, BS EN 62680-1-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

