



Della

Della 80W High power LED flood light

The Della are Kosnic's standard LED floodlight range and make ideal replacements for energy-hungry halogen lighting. Suitable for outdoor use, the range offers quality aluminium products with high lumen efficiency and a long life.

KFLDHS80Q65-W65-BLK ()

Specification

Voltage	220-240 Vac 50-60 Hz
Voltage (eg 220-240 Vac 50/60Hz)	220-240Vac 50/60Hz
Current (mA)	351
Rated Power (W)	80
CCT Words	Day Light
CCT (K)	6500
Beam Angle(°)	110
Nominal Lifetime (h)	40000
Total Luminous Flux (lm)	8000
Power Factor	0.99
SDCM of CCT	<6
Dimensions L x W x D (mm)	282 x 276 x 38 (mounting surface to face 154mm)
Weight (kg)	1.9
In-rush current (peak/duration) (A)	1.7 / 80 us
Protection Rating	Class I
IP Rating	IP65
Ambient Temperature Range (°C)	-20 to 40

Light Source Specification

Dimmable (Y/N/Specific dimmer)	N
CRI	82
Lumen Maintenance Factor (x.xx)	0.7

Optional Gears and Accessories

Component 1	Connection - 1m of H05RN-F 3 x 1.0mm ² cable
Component 2	In-Line Connector KCWP3IN

Technical Drawings

