219.3233

PLUG
32A 2P+E 6h 200-250V 60Hz 50Hz II 2GD Mantle terminals Low temperature [-50°C]

* Product image may be indicative

EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)
EN 60079-0 (2018)
IEC 60079-0 (2017)
IEC 60079-31 (2013)
EN 60079-7 (2015)
EN 60309-4 (2007)
EN 60309-4/A1 (2012)
EN 60079-31 (2014)
EN IEC 60079-7/A1 (2018)
IEC 60079-7 (2017)
EN 60079-1 (2014)
IEC 60079-1 (2014)

ATEX directive 2014/34/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-EX[GD] Series
Synthetical description	PLUG
Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

EX CHARACTERISTICS

Group and categories EX	II 2GD

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP66
Impact resistance	7J
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND
Ambient temperature Ta min	-50 °C
Ambient temperature Ta max	60 °C

DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual
Instruction manual
Instruction manual

OPTIONS & VARIOUS NOTES

Options	Low temperature [-50°C]
Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.

SCAME PARRE S.p.A
Via Costa Erta, 15 - 24020 Parre (BG) Italy - +39 035 705000