

OMNI FILAMENT GLS BULB B22 1055LM 7.8W 2700K NON-DIMM 330 BEAM
CLEAR FULL GLASS INTEGRAL

ILGLSB22NC039



General

Warranty (Years)	2
Product Type	GLS

Physical Data

Globe Type	GLS
Bulb Base	B22
Base Term	Bayonet cap
Construction	Glass shell, Filament strip, Aluminium base

Light Data

Luminous Flux in Lumens (lm)	1055
Luminous efficacy (lm/W)	135
Instant on (Less than 1 second)	Yes
Correlated Colour Temperature (CCT) (K)	2700
Colour Temperature Name	Warm
Beam Angle (Range)	220+
Switching cycles	7500
Lifetime (hours)	15000
LED Type	Filament chip
Colour Rendering Index (CRI)	80
Beam Angle	330
Lumens Range	850 to 1500

Electrical Data

Power Consumption (Range)	5 to 8
Input Current (A)	66

Wattage equivalent (W)	75
Power Factor	0.5
Power Consumption (w)	8.5
Voltage Range (v)	220-240

Environmental

New Energy Rating	D
IP Rating (Ingress Protection)	IP20 IP20
Previous Energy Rating	A++

Electrical Data, Environmental

EN	EN-62560
LVD Certified	Yes

Product Specification

Warranty (Years)	2
Housing Material	Aluminium, Glass

Key Features

Bullet 1	Filament technology with super-wide beam angle
Bullet 2	Warm Light
Bullet 3	1055 Lumens
Bullet 4	Non-Dimmable

Environmental Specification

Minimum operating temperature (degrees Celcius)	-20
Maximum operating temperature (degrees Celcius)	40