

**GLS BULB WITH DUSK TO DAWN DUAL SENSOR B22 806LM 8W 2700K NON-DIMM 240 BEAM FROSTED INTEGRAL**

ILGLSB22SC042



**General**

<b>Warranty (Years)</b>	3
<b>Product Type</b>	GLS

**Physical Data**

<b>Globe Type</b>	GLS
<b>Bulb Base</b>	B22
<b>Base Term</b>	Bayonet cap
<b>Construction</b>	Plastic and Aluminium heat sink, polycarbonate diffuser

**Light Data**

<b>Luminous Flux in Lumens (lm)</b>	806
<b>Luminous efficacy (lm/W)</b>	101
<b>Instant on (Less than 1 second)</b>	Yes
<b>Correlated Colour Temperature (CCT) (K)</b>	2700
<b>Colour Temperature Name</b>	Warm
<b>Beam Angle (Range)</b>	220+
<b>Lifetime (hours)</b>	15000
<b>LED Type</b>	Surface mounted device (SMD)
<b>Colour Rendering Index (CRI)</b>	80
<b>Beam Angle</b>	240
<b>Lumens Range</b>	470 to 850

**Electrical Data**

<b>Power Consumption (Range)</b>	5 to 8 8 to 15
<b>Input Current (A)</b>	55
<b>Wattage equivalent (W)</b>	60

<b>Power Factor</b>	0.5
<b>Power Consumption (w)</b>	8
<b>Voltage Range (v)</b>	220-240

**Environmental**

<b>New Energy Rating</b>	F
<b>IP Rating (Ingress Protection)</b>	IP20 IP20
<b>Previous Energy Rating</b>	A+

**Electrical Data, Environmental**

<b>EN</b>	EN-62560
<b>LVD Certified</b>	Yes

**Product Specification**

<b>Warranty (Years)</b>	3
<b>Housing Material</b>	Aluminium, Polycarbonate

**Key Features**

<b>Bullet 1</b>	Auto On and Off Sensor
<b>Bullet 2</b>	Warm Light
<b>Bullet 3</b>	806 Lumens
<b>Bullet 4</b>	Non-Dimmable

**Environmental Specification**

<b>Minimum operating temperature (degrees Celcius)</b>	-20
<b>Maximum operating temperature (degrees Celcius)</b>	40