

# OMNI FILAMENT GOLF BALL BULB E27 470LM 4.2W 2700K NON-DIMM 320 BEAM CLEAR INTEGRAL

ILGOLFE27NC029



Integral Filament Omni Lamps utilise Filament LED technology and a full-glass body to create a decorative look and wide beam angle that looks fantastic in chandeliers and fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

#### **Details**

Quick Order Code: 568248

**Barcode**: 5055788215431

Category:LampsRange Name:OmniProduct Type:Mini Globe

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

#### **Physical Data**

Product Length (mm): 82
Product Width (mm): 45
Product Weight (g): 23

Material:Aluminium, GlassBase Term:Edison screw

Bulb Base: E27

**Construction:** Glass shell, Filament strip, Aluminium base

Globe Finish: Clear
Globe Type: Golf Ball

Bulb Fixing: Pendant, Wall, lamp stand, table lamp

Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

#### **Electrical Data**

Power (W): 4.2
Power Consumption (W): 4.2
Power Factor: 0.4
Wattage equivalent (W): 40

Amperage (mA): 40

**Dimming:** Non-Dimmable

Driver Included: Yes
Electric Current: AC

**EN:** EN-62560

LVD Certified: Yes

## **Light Data**

Luminous Flux in Lumens (Im): 470
Luminous efficacy (Im/W): 112
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:320Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


**LED Type:** Filament chip


Lifetime (hours): 15000 Switching Cycles: 7500

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating:** A+ E **New Energy Rating:** Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 Maximum Operating Temperature (°C): 40





### **Packaging**

## Portal.integral-led.com

Package Length (mm): 50
Package Width (mm): 50
Package Depth (mm): 90