



### Daily time switch 1 channel, digital, 1 module

#### Technical Characteristics

Fixing mode	Din-Rail
Switch mode	change-over contact
Rated operational voltage Ue	230 V
Frequency	50 Hz
Supply voltage	230V AC
Depth of installed product	64 mm
Height of installed product	92 mm
Width of installed product	18 mm
	18 mm
	92 mm
Dimensions (W x H x D)	64 mm
Power consumed	1 VA
Total power loss under IN	1 W
Power dissipation per coil	1 W
Breaking capacity	16A 250V AC1
Number of modules	1
Power reserve [years]	≈ 3 a
Max. power with incandescent lamps	1000 W
Mounting type	din-Rail
Connection cross-sect. flexible conductor	1 / 4mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 4mm <sup>2</sup>
Type of connection	with screw
Number of contacts	1
Type of contacts	1 changeover
Type of connection	with screw terminals
Summer / Winter time change	manual
Shortest switching time	1 mn
Type of programming	digital
Programming cycle	24H
Number of channels	1
Supply failure reserve	3 years
With holidays program	No
DCF	No
Cycle	daily
Protection index IP	IP20
	-10 °C
Operating temperature	50 °C

