

MTN140

MCB 1P 6kA B-40A 1M



- Architecture
 - Number of poles
1 P
 - Type of pole
1 P
 - Curve
B
- Main electrical features
 - Rated operational voltage U_e
230 / 400 V
 - Frequency
50;60 Hz
 - Rated current
40 A
 - Type of supply voltage
AC
- Voltage
 - Rated insulation voltage
500 V
 - Rated impulse withstand voltage
4000 V
- Electric current
 - Rated service breaking capacity I_{cs} AC according IEC 60898-1
6 kA
- Electric current / temperature
 - Rating current 30°C
40 A

- Dimensions
 - Depth of installed product
70 mm
 - Height of installed product
83 mm
 - Width of installed product
17.5 mm
- Power
 - Total power loss under IN
4.8 W
- Endurance
 - Electric endurance in number of cycles
4000
 - Number of mechanical operations
20000
- Capacity
 - Number of modules
1
- Installation, mounting
 - Tightening torque
2,8Nm
- Connection
 - Connection cross-sect. flexible conductor
1 ; 25mm²
 - Connection cross-sect. rigid cable
1 ; 35mm²
 - Type of connection
with screw
- Standards
 - Standard text
EN 60898-1
 - European directive WEEE
concerned
- Safety
 - Protection index IP
IP20
- Use conditions
 - Operating temperature
-25/70 °C
 - Storage temperature
-25/80 °C
- Temperature
 - Operating temperature
-25/70 °C