

ADC140

RCBO Electronic 1M 1P 10kA C-40A 30mA AC Class



- Architecture
 - Neutral position right
 - Number of poles 1 P
 - Type of pole 1 P
 - Curve C
- Main electrical features
 - Rated operational voltage U_e 230 / 240 V
 - Frequency 50 Hz
 - Rated current 40 A
- Voltage
 - Rated insulation voltage 250 V
 - Max operating voltage 253 V
 - Rated impulse withstand voltage 4000 V
- Electric current
 - Rated residual operating current 30 mA
 - Breaking and opening capacity

- 6 kA
- Electric current / temperature
 - Rating current 30°C
40 A
- Dimensions
 - Depth of installed product
73 mm
 - Height of installed product
115 mm
 - Width of installed product
17.8 mm
- Power
 - Total power loss under IN
12.96 W
- Endurance
 - Electric endurance in number of cycles
2000
 - Number of mechanical operations
1000
- Capacity
 - Number of modules
1
- Installation, mounting
 - Tightening torque
2,1Nm
- Standards
 - Standard text
IEC 61009-1 ; EN 61009-1
 - European directive WEEE
concerned
- Safety
 - Protection index IP
IP20
 - Residual current type
AC
- Temperature
 - Operating temperature
-5/60 °C