

## **IP44 Industrial Plugs 16A - 32A**

### Specifications and Dimensions

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to. Terminals, including factory fitted, should be checked periodically to ensure correct tightness. **DO NOT USE POWER TOOLS ON THESE PRODUCTS.**

ERIS offers a comprehensive range of industrial plugs and sockets ranging from 16A to 125A to suit all environments and applications. All products are RoHS compliant and are produced strictly according to international standard IEC 60309-1, IEC 60309-2.

ERIS Plugs and sockets are manufactured to be used in a wide variety of industry from Petroleum and Chemical industry, quarry plants, airports, building sites, processing industry, water and sewerage plants, hotel, ports and mining.

The ERIS plugs and sockets are corrosion and impact resistant, IP rated – sealed against levels of dust and water ingress. Products have an operating temperature range of -25°C to 50°C.

All products have an operating voltage up to 690V AC in varying pin configurations and are also colour coded to identify operation voltage.

For any further comments or assistance please contact:


**[eris-eu.com](http://eris-eu.com)**



**Industrial**

# IP44 Industrial Plugs 16A-32A

## Specifications and Dimensions




Product Code	Product Description
ERS1631P	16A 2P+E 110V
ERS1632P	16A 2P+E 240V
ERS1644P	16A 3P+E 415V
ERS1654P	16A 3P+N+E 415V

Product Code	Product Description
ERS3231P	32A 2P+E 110V
ERS3232P	32A 2P+E 240V
ERS3244P	32A 3P+E 415V
ERS3254P	32A 3P+N+E 415V

**Dimensions:**

Current	16A			32A		
	3	4	5	3	4	5
Pole	3	4	5	3	4	5
A (mm)	124	133	136	153.5	153.5	159.5
B (mm)	58	65.5	73.5	78	78	82.5
C (mm)	15.5	15.5	17	22	22	22
D (mm)	51	58.5	64.5	66.5	66.5	74
Cable size (mm <sup>2</sup> )	1~2.5			2.5~6		



Available in the following pin options:

3 Pin: 2P+E
4 Pin: 3P+E
5 Pin: 3P+N+E

For any further comments or assistance please contact:

**[eris-eu.com](http://eris-eu.com)**