

LED Highbay Accessories

Aluminium 60° Reflector

- 60° pure aluminium reflector, suitable for high mounting positions
- Innovative 3 point keyhole mounting mechanism

Aluminium 90° Reflector

- 90° pure aluminium reflector, suitable for medium to high mounting positions
- Innovative 3 point keyhole mounting mechanism

Acrylic 70° Reflector

- 70° acrylic reflector, suitable for retail and other applications which require directional light spill
- Includes fixing ring and 3 point mounting mechanism

Microwave Sensor

- Automatic presence detection and dimming when used with 1-10V dimmable LED drivers
- Mounting height up to 15m. Sensor functions can be adjusted using internal DIP switches
- Includes fixing clips for both direct to Highbay or Reflector mounting.
- Refer to installation guide for further details



Measurement Part No. Description Weight Function A x B* Aluminium Reflector - 60° 355 x 150mm LXHB-REFM-60 0.4 Kg Improved beam control - use in high mounting positions or narrow aisle areas LXHB-REFM-90 Aluminium Reflector - 90° 355 x 150mm 0.55 Kg Improved beam control - use in medium to high mounting positions in open areas LXHB-REFA-70 Acrylic Reflector - 70° 410 x 275mm 1.1 Kg Reeded diffuser - allows directional light spill through the translucent material LXHB-MSB 72 x 59mm Microwave Sensor - Black 0.35 Kg Direct to Highbay or Reflector mounting - Motion and Daylight sensor, IP65, 1-10V dim LXHB-MSW Microwave Sensor - White 72 x 59mm 0.35 Kg Direct to Highbay or Reflector mounting - Motion and Daylight sensor, IP65, 1-10V dim 180 x 25mm LXHB-WG Wire Guard 0.20 Kg Attach to Highbay lens ring for improved impact resistance I XHB-FPI Frosted Polycarbonate Lens 155 x 5mm 0.10 Kg Replaces tempered glass cover for use in food industry areas * Measurement: A= Outer diameter, B= Height

Reflector mounting



Email sales@luxna.co.uk

