

GX53 BULB 470LM 5W 4000K NON-DIMM 110 BEAM FROSTED INTEGRAL

ILGX53N002



Integral LED GX53 lamps are an ideal retrofit lamp for GX53 fittings in kitchen units, display cabinets and under-shelf lighting. These highly efficient lamps offer significant energy savings and long life compared to halogen equivalents.

Details

Quick Order Code: 378588

Barcode: 5055788222941

Category:LampsRange Name:GX53Product Type:GX53

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

Physical Data

Product Length (mm): 25
Product Width (mm): 75
Product Weight (g): 50

Material: Aluminium, Polycarbonate

Base Term: GX53 Bulb Base: GX53

Construction: SMD, Plastic Body

Globe Finish: Frosted Globe Type: GX53

Bulb Fixing: Under Shelf Lighting, Display Cabinets

Bulb or Luminaire Shape: Round

Placement / Application: Indoor, Outdoor, General Lighting

Electrical Data

Power (W): 5
Power Consumption (W): 5
Power Factor: 0.5
Voltage Range (v): 220-240
Wattage equivalent (W): 40

Amperage (mA): 40

Dimming: Non-Dimmable

Driver Included: Yes
Electric Current: AC

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 470
Luminous efficacy (Im/W): 94
Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature: 4000K - Cool White

Colour Temperature Name: Cool White

Beam Angle: 110
Colour Rendering Index (CRI): 80
Frequency Range (Hz): 50/60
Instant on (Less than 1 second): Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 15000 Switching Cycles: 50000

Environment

EN: EN-62560

LVD Certified: Yes
CE RoHS: Yes
Previous Energy Rating: A+
New Energy Rating: F
Hg 0% (Mercury Free): Yes
IP Rating (Ingress Protection): IP20
Lowest Operating Temperature (°C): -20
Maximum Operating Temperature (°C): 40





Packaging

Portal.integral-led.com

Package Length (mm):75Package Width (mm):75Package Depth (mm):26Qty per euro pallet:4800