


DATASHEET



WW15C

230V 15W Round LED Recessed Adjustable Downlight

www.mlaccessories.co.uk



MLA PART CODE	WW15C
DESCRIPTION	230V 15W Round LED Recessed Adjustable Downlight
NET WEIGHT (KG)	0.741
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 157 Projection - 87 Recessed Depth - 98 Minimum Void - 150
CUT-OUT (MM)	Cut-out Diameter - 134
TILT (DEGREES)	40
ROTATION (DEGREES)	350
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP40 (IP20 from above)
WATTAGE (W)	15
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	1500
LUMENS LIGHT SOURCE ONLY (LM)	1500
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	100.48
CIRCUIT WATTAGE (W)	14.59
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.017

PST-LM	0.1
BEAM ANGLE (DEGREES)	40
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	54,000
DIMMABLE	No
IC RATED	No
OPERATING TEMPERATURE	35°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 18W OUTPUT VOLTAGE - 30-42V OUTPUT CURRENT - 350mA POWER FACTOR - >0.9 EFFICIENCY FULL LOAD - 83.4 AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832952855

Date Created: 25/04/2022 09:39

