

Product Code: CMA20404



Technical Specification

0 0 **General Information** Plate Dimensions (mm) 146 (W) x 86 (H) x 9 (D) Plate Fixing Centres - Horizontal (mm) 120.6 Style Mode Finish Polar White Materials Front Plate: Urea Fixing Lugs: Brass Anti Microbial Certified Yes Yoke Required No Minimum Back Box Depth (mm) 25 Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years) 10 Standards BS 5733: 2010 +A1: 2014 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Description: 4 Gang GridPro® Frontplate

