

CNS 200 Trend UK

CONVECTOR HEATERS

PRODUCT-NO.: 236563

CNS 200 Trend UK wall convector – because heating should not be a question of space.

Sometimes there's just not much room – even for heater. This is why the CNS 200 Trend UK wall convector is very slender. At only 10 cm deep, it nevertheless generates excellent levels of thermal comfort. The CNS 200 Trend UK blends ever so discreetly into its surroundings, efficiently delivering cosy warmth. The comfort functions of the integral controller, such as the 7-day timer, frost protection and open window detection, highlight the efficiency and high quality features of the wall convector.



The main features

Wall mounted convector – ideal as a booster heater or interim heater for spring/autumn

2000 W heating output

Even, quiet room air heating

Metal casing and slimline design

Controls with backlit LCD

7-day timer, frost protection and open window detection

Control unit with self-learning capability: Automatic calculation of the preheat time in timer mode

ON/OFF switch and overheating protection



Type	CNS 50 Trend UK	CNS 75 Trend UK	CNS 100 Trend UK
Part no.	236559	236560	236561
Connected load	0,5 kW	0,75 kW	1,0 kW
Width	348 mm	426 mm	426 mm
Depth	100 mm	100 mm	100 mm
Height	450 mm	450 mm	450 mm

Technical data

Power supply	{1/N/PE ~240V}	{1/N/PE ~240V}	{1/N/PE ~240V}
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated voltage	240 V	240 V	240 V
Rated current	2,1 A	3,1 A	4,2 A
Setting range	5-30 °C	5-30 °C	5-30 °C
IP-Rating	IP24	IP24	IP24
Protection class	I	I	I
Weight	4 kg	4,6 kg	4,6 kg
Colour	alpine white	alpine white	alpine white



Type	CNS 150 Trend UK	CNS 200 Trend UK	CNS 250 Trend UK
Part no.	236562	236563	236564
Connected load	1,5 kW	2,0 kW	2,5 kW
Width	582 mm	738 mm	894 mm
Depth	100 mm	100 mm	100 mm
Height	450 mm	450 mm	450 mm

Technical data

Power supply	{1/N/PE ~240V}	{1/N/PE ~240V}	{1/N/PE ~240V}
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated voltage	240 V	240 V	240 V
Rated current	6,3 A	8,3 A	10,4 A
Setting range	5-30 °C	5-30 °C	5-30 °C
IP-Rating	IP24	IP24	IP24
Protection class	I	I	I
Weight	6 kg	7,7 kg	9,2 kg
Colour	alpine white	alpine white	alpine white



Type	CNS 300 Trend UK
Part no.	236565
Connected load	3,0 kW
Width	1050 mm
Depth	100 mm
Height	450 mm

Technical data

Power supply	{1/N/PE ~240V}
Frequency	50/- Hz
Rated voltage	~240 V
Rated current	12,5 A
Setting range	5-30 °C
IP-Rating	IP24
Protection class	I
Weight	10,9 kg
Colour	alpine white

Depth including 22 mm wall retainer

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.