


CNS 300 Trend UK

CONVECTOR HEATERS

PRODUCT-NO.: 236565

CNS 300 Trend UK wall convector – because heating should not be a question of space.

Sometimes there's just not much room – even for heater. This is why the CNS 300 Trend UK wall convector is very slender. At only 10 cm deep, it nevertheless generates excellent levels of thermal comfort. The CNS 300 Trend UK blends ever so discreetly into its surroundings, efficiently delivering cosy warmth. The comfort functions of the integral controller, such as the 7-day timer, frost protection and open window detection, highlight the efficiency and high quality features of the wall convector.



The main features

Wall mounted convector – ideal as a booster heater or interim heater for spring/autumn

3000 W heating output

Even, quiet room air heating

Metal casing and slimline design

Controls with backlit LCD

7-day timer, frost protection and open window detection

Control unit with self-learning capability: Automatic calculation of the preheat time in timer mode

ON/OFF switch and overheating protection



| Type | CNS 50 Trend UK | CNS 75 Trend UK | CNS 100 Trend UK |
|----------------|-----------------|-----------------|------------------|
| Part no. | 236559 | 236560 | 236561 |
| Connected load | 0,5 kW | 0,75 kW | 1,0 kW |
| Width | 348 mm | 426 mm | 426 mm |
| Depth | 100 mm | 100 mm | 100 mm |
| Height | 450 mm | 450 mm | 450 mm |

Technical data


| | | | |
|------------------|----------------|----------------|----------------|
| Power supply | {1/N/PE ~240V} | {1/N/PE ~240V} | {1/N/PE ~240V} |
| Frequency | 50/- Hz | 50/- Hz | 50/- Hz |
| Rated voltage | 240 V | 240 V | 240 V |
| Rated current | 2,1 A | 3,1 A | 4,2 A |
| Setting range | 5-30 °C | 5-30 °C | 5-30 °C |
| IP-Rating | IP24 | IP24 | IP24 |
| Protection class | I | I | I |
| Weight | 4 kg | 4,6 kg | 4,6 kg |
| Colour | alpine white | alpine white | alpine white |



| Type | CNS 150 Trend UK | CNS 200 Trend UK | CNS 250 Trend UK |
|----------------|------------------|------------------|------------------|
| Part no. | 236562 | 236563 | 236564 |
| Connected load | 1,5 kW | 2,0 kW | 2,5 kW |
| Width | 582 mm | 738 mm | 894 mm |
| Depth | 100 mm | 100 mm | 100 mm |
| Height | 450 mm | 450 mm | 450 mm |

Technical data

| | | | |
|------------------|----------------|----------------|----------------|
| Power supply | {1/N/PE ~240V} | {1/N/PE ~240V} | {1/N/PE ~240V} |
| Frequency | 50/- Hz | 50/- Hz | 50/- Hz |
| Rated voltage | 240 V | 240 V | 240 V |
| Rated current | 6,3 A | 8,3 A | 10,4 A |
| Setting range | 5-30 °C | 5-30 °C | 5-30 °C |
| IP-Rating | IP24 | IP24 | IP24 |
| Protection class | I | I | I |
| Weight | 6 kg | 7,7 kg | 9,2 kg |
| Colour | alpine white | alpine white | alpine white |



| | |
|----------------|------------------|
| Type | CNS 300 Trend UK |
| Part no. | 236565 |
| Connected load | 3,0 kW |
| Width | 1050 mm |
| Depth | 100 mm |
| Height | 450 mm |

Technical data

| | |
|------------------|----------------|
| Power supply | {1/N/PE ~240V} |
| Frequency | 50/- Hz |
| Rated voltage | ~240 V |
| Rated current | 12,5 A |
| Setting range | 5-30 °C |
| IP-Rating | IP24 |
| Protection class | I |
| Weight | 10,9 kg |
| Colour | alpine white |

Depth including 22 mm wall retainer

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.