#### Part number

## JKF 03

**Technical data** 





Female insert, JK series, screw terminal connection, 3 poles + PE, 10 A 230/400 V 4 kV 3, size "21.21"

Product description	
Product type	Insert
Series	JK
Connection type	Screw terminal connection
Gender	Female
N. of poles	3 poles + 🖃
Size	Size "21.21"

Current	10 A
Voltage	230 - 400 V
Rated impulse withstand voltage	4 kV
Pollution degree	3
Rated voltage according to UL/CSA	600V

- 2,50 mm <sup>2</sup>
-

**AWG size** 18 - 14

**Characteristics** 10A 230/400V 4kV 3; 10A 400/690V **according to EN 61984** 4kV 2

Mating cycles≥ 200Insulation resistance≥ 10 GΩWeight15,75 g

Operating

temperature range

(min, max)

UL 94 flammability

rating

≥ 200

-40°C ... +100°C

quantity

Material properties

Main material Polycar

Main materialPolycarbonate (PC)Other materialsContacts: copper alloy

**Colour** RAL 7035 grey

Compliant with exemption

**RoHs conformity** 6(c): copper alloy containing up to 4%

lead by weight

China RoHs - EFUP 50
REACH SVHC Yes
substances Lead

**Approvals / Standards** 

**Reference standard** EN 61984:2009-06

Certifications CSA, CQC, DNV-GL, BV, EAC

UL ECBT2
General ordering information

**EAN13 code** 8015747209434

**Packaging Information** 

Packaging length210,00 mmPackaging height200,00 mmPackaging width130,00 mmPackaging weight2,95 kgPackaging volume5,46 dm³Packaging descriptionCarton boxPackaging quantity200 PcsPackaging EAN code8015747209595

Packaging EAN Code 6015/4/205

Sub-packaging weight 0,59 kg

**Sub-packaging** Carton tray

Sub-packaging 40 quantity

Sub-packaging EAN

barcode

40 Pcs

8015747209601

### Part number

# JKF 03



### **Notes**

Dimensions shown in mm are not binding and may be changed without notice.

### **California Proposition 65 Information**



### WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.