

SFX/ISP2-LSF-GRY

ISP2 2pr 22AWG Individual Foil Screen 600V Grey LSF (8723)



| | |
|------------------------------------|--|
| Cable Construction | 2 Pairs |
| Conductor | Tinned Copper |
| Conductor Diameter (mm) | 0.24 ±0.008 x 7 |
| Stranded Diameter (mm) | 0.76 |
| Insulation | FPE |
| Insulation Thickness (mm) | 0.24 |
| Insulation Diameter (mm) | 1.20 ±0.10 |
| Insulation Colours | Red,Black;Green,White |
| Al-PET Shield | ≥115% (On each pair) |
| Drain Wire | |
| Conductor | Tinned Copper |
| Conductor Diameter (mm) | 0.19 ±0.008 x 7 |
| Nylon Rip-Cord | White 210D |
| Jacket | LSF |
| Jacket Thickness (mm) | 0.550 |
| Overall Diameter (mm) | 4.30 ±0.20 |
| Jacket Colour | Grey RAL 7042 |
| Sheath Printing | ISP2 2x2x22AWG 600V Individually Screened LSF RoHS2 (PO) (m) |
| Reaction to Fire | Eca |
| Electrical Characteristics | |
| Max Conductor DC resistance @ 20°C | <50Ω/km |
| Rated Temperature | 80°C |
| Rated Voltage | 600V |
| Insulation Resistance @20°C | >200MΩ/km |