



Metal Clad Wall / Floor Mounted Transformers

Technical Data

- Single phase double wound safety isolating transformer.
- Enclosed to IP22.
- 230V AC 1-Ph hard wired to 6mm² terminal blocks. 110V AC secondary. Protected by a manually resettable thermal overload cut out switch.
- 50/60Hz
- Sheet steel vented suitable for wall or floor mounting to IP22.
- Hammer grey powder coat finish.

For any further comments or assistance please contact:

eris-eu.com



Part Number	Output Connection
ERSWM1500/2	2 x 16A 110V Sockets, IEC 60309 (BS4343)
ERSWM1500	Internal Hard Wire 0.5 to 6.0mm ²
ERSWM3300/2	2 x 16A 110V Sockets, IEC 60309 (BS4343)
ERSWM3300	Internal Hard Wire 0.5 to 6.0mm ²
ERSWM5000/4	4 x 16A 110V Sockets, IEC 60309 (BS4343)
ERSWM5000	Internal Hard Wire 0.5 to 6.0mm ²

Part Number	Rating	Weight (Aprx)	Dimensions (mm)		
			Height	Width	Depth
ERSWM1500/2	1.5KVA Intermittent (5 mins on, 15mins off) 0.75KVA continuous	10kg	245	275	250
ERSWM1500	1.5KVA Intermittent (5 mins on, 15mins off) 0.75KVA continuous	10kg	245	275	185
ERSWM3300/2	3.3KVA Intermittent (5mins on 10mins off) 1.65KVA continuous	16kg	245	275	250
ERSWM3300	3.3KVA Intermittent (5mins on 15mins off) 1.65KVA continuous	16kg	245	275	185
ERSWM5000/4	5KVA Intermittent (5 mins on, 15mins off) 2.5KVA continuous	30kg	275	340	285
ERSWM5000	5KVA Intermittent (5 mins on, 15mins off) 2.5KVA continuous	30kg	275	337	225

For any further comments or assistance please contact:

eris-eu.com