



Polypropylene Conduit

Specifications and Dimensions

Available in a diameter range of 16-50mm and lengths of 10-100m

- Material: Polypropylene
- Ingress protection: IP40
- Colour: Black or White
- 16mm: UL 94 HB Self-extinguishing, Temperature range -15°C to +90°C
- 20, 25 & 32mm: Low Smoke Zero Halogen, Temperature range -40°C to +120°C
- 40 & 50mm: Halogen Free, Temperature range -15°C to +90°C

Part No	Size	Colour	Int. ø	Ext. ø
ERS16PP10MB	16mm x 10m	Black	12mm	16mm
ERS16PP25MB	16mm x 25m	Black	12mm	16mm
ERS16PP50MB	16mm x 50m	Black	12mm	16mm
ERS16PP100MB	16mm x 100m	Black	12mm	16mm
ERS20PP10MB	20mm x 10m	Black	16.8mm	20mm
ERS20PP25MB	20mm x 25m	Black	16.8mm	20mm
ERS20PP50MB	20mm x 50m	Black	16.8mm	20mm
ERS20PP100MB	20mm x 100m	Black	16.8mm	20mm
ERS20PP10MW	20mm x 10m	White	16.8mm	20mm
ERS20PP25MW	20mm x 25m	White	16.8mm	20mm
ERS20PP50MW	20mm x 50m	White	16.8mm	20mm
ERS20PP100MW	20mm x 100m	White	16.8mm	20mm

Part No	Size	Colour	Int. ø	Ext. ø
ERS25PP10MB	25mm x 10m	Black	19.9mm	25mm
ERS25PP25MB	25mm x 25m	Black	19.9mm	25mm
ERS25PP50MB	25mm x 50m	Black	19.9mm	25mm
ERS25PP100MB	25mm x 100m	Black	19.9mm	25mm
ERS25PP10MW	25mm x 10m	White	19.9mm	25mm
ERS25PP25MW	25mm x 25m	White	19.9mm	25mm
ERS25PP50MW	25mm x 50m	White	19.9mm	25mm
ERS25PP100MW	25mm x 100m	White	19.9mm	25mm
ERS32PP10MB	32mm x 10m	Black	26.5mm	32mm
ERS32PP25MB	32mm x 25m	Black	26.5mm	32mm
ERS32PP50MB	32mm x 50m	Black	26.5mm	32mm
ERS40PP25MB	40mm x 25m	Black	31mm	40mm
ERS50PP25MB	50mm x 25m	Black	39mm	50mm

For any further comments or assistance please contact:

eris-eu.com