



Enclosed Switch Fuses, 3 Pole + Neutral, IP65

Technical Data

- Padlockable in the off position
- Defeatable door interlocked handle
- IP20 Terminal protection included
- Conforms to IEC/EN 60947-1 & 3
- Supplied complete with fuses
- Bureau Veritas, KEMA certified, UKCA/CE Approved

Metal Enclosed Switch Fuses

- 125 to 800 Amp AC21
- 3 Pole & Switched Neutral (4th Pole)
- IP65 RAL7035 Metal weatherproof enclosure
- Removable top and bottom gland plates
- Door earth lead fitted as standard

GRP Enclosed Switch Fuses

- 125 to 400 Amp AC21
- 3 Pole & Switched Neutral (4th Pole)
- IP65 RAL7035 GRP weatherproof enclosure
- IK10 impact protection

For any further comments or assistance please contact:

eris-eu.com



Metal Enclosed Switch Fuses

Data	AMPS AC21	AMPS AC23	3pH Motor Rating	BS Fuse Size	Enclosure Dimensions
ERSMSF1253PN	125A	125A	55kW	A3	400 x 400 x 200mm
ERSMSF1603PN	160A	160A	90kW	B1-B2	500 x 400 x 200mm
ERSMSF2003PN	200A	200A	110kW	B1-B2	500 x 400 x 200mm
ERSMSF2503PN	250A	250A	132kW	B1-B2	500 x 400 x 200mm
ERSMSF3153PN	315A	315A	160kW	B1-B3	800 x 600 x 300mm
ERSMSF4003PN	400A	400A	220kW	B1-B4	800 x 600 x 300mm
ERSMSF6303PN	630A	630A	355kW	C1-C2	1000 x 800 x 300mm
ERSMSF8003PN	800A	800A	355kW	C1-C3	1000 x 800 x 300mm

GRP Enclosed Switch Fuses

Data	AMPS AC21	AMPS AC23	3pH Motor Rating	BS Fuse Size	Enclosure Dimensions
ERSGSF1253PN	125A	125A	55kW	A3	400 x 400 x 200mm
ERSGSF1603PN	160A	160A	90kW	B1-B2	500 x 400 x 200mm
ERSGSF2003PN	200A	200A	110kW	B1-B2	500 x 400 x 200mm
ERSGSF2503PN	250A	250A	132kW	B1-B2	500 x 400 x 200mm
ERSGSF3153PN	315A	315A	160kW	B1-B3	800 x 600 x 300mm
ERSGSF4003PN	400A	400A	220kW	B1-B4	800 x 600 x 300mm

For any further comments or assistance please contact:

eris-eu.com