

## MR11 GU4 BULB 380LM 3.4W 4000K NON-DIMM 36 BEAM INTEGRAL

ILMR11NE010



This 3.7W retro-fit Integral LED MR11 delivers brightness similar to a 35W halogen bulb, in cool white light. It features four high output LEDs, an anti-glare refractor, all finished with a plastic thermally efficient body. The ideal lamp for commercial and home use.

### **Details**

Quick Order Code: 564732

**Barcode**: 5055788234890

Category: Lamps

Range Name: 12V GU4 Base

Product Type: MR11

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

### **Physical Data**

Product Length (mm): 38
Product Width (mm): 35
Product Weight (g): 18

Optic: Refractor Cover for enhanced light distribution

Material:PlasticBase Term:GU4Bulb Base:MR11

**Construction:** Plastic White, Plastic diffuser

Globe Finish: Clear
Bulb Fixing: Downlight
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting
Spot Type: High Power Three LED

## **Electrical Data**

Power (W): 3.7
Power Consumption (W): 3.7
Power Factor: 0.4
Voltage Range (v): 12

Wattage equivalent (W): 35
Amperage (mA): 470

**Dimming:** Non-Dimmable

**Driver IC Manufacturer:** Silergy

**Driver Included:**No, needs 12V AC Transformer

Electric Current: AC
True Wattage Eq (W): 35

**EN:** EN-62560

LVD Certified: Yes

# **Light Data**

Luminous Flux in Lumens (Im): 380
Luminous efficacy (Im/W): 93
Peak Intensity (Cd): 850
Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature: 4000K - Cool White

Colour Temperature Name: Cool White

Beam Angle:36Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


**LED Type:** Surface mounted device (SMD)

Lifetime (hours): 15000
Switching Cycles: 50000
Useful Lumens (lm): 345

### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating:** A++ F **New Energy Rating:** Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40



# ILMR11NE010 A B C D E F G 4 kWh/1000h

# **Packaging**

Package Weight (g): 30
Package Length (mm): 50
Package Width (mm): 35
Package Depth (mm): 35
Qty per euro pallet: 10500