

LED100FLWHE

10W LED Compact Floodlight Single Flood – White

Features & Benefits

- 1x 10W Powerful LED compact floodlight
- Pan and tilt light aiming adjustment
- IP55 weatherproof rating
- Manual override
- Optional wall mount spacer available: 907-0-988



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to +45°C
Ingress Protection Rating	IP55
Wattage	10
Beam Angle	90° x 90°
Pan & Tilt Adjustment	Pan Left 40°, Pan Right 40° (Without Spacer). Pan Left 45°, Pan Right 45° (With Spacer)
Energy Efficiency	Class G
Energy Usage	10KwH/1000H

Data sheet

LED100FLWHE

Light / LED Lighting

Lumen output (lm)	840
Colour Temperature (K)	4000
LED Type	SMD (Intergrated)
Mounting Hole Centres (mm)	60
Multiple Unit Support	Yes
Cable Entry(s)	Bottom Entry (Knockouts), Back Entry

General

Weight (g)	287
Height (mm)	160
Width (mm)	80
Depth (mm)	50
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings, Setting Knob
Accessories (Optional)	Corner mount bracket (907.0.756), Wall spacer (907.0.971)
EAN Number	5012483014097
Guarantee Period	3 Years

Data sheet

LED100FLWHE

Light / LED Lighting

Line Diagrams

