

LED200FLBE

2x 10W LED Compact Floodlight Twin Flood – Black



Features & Benefits

- 2x 10W Powerful LED compact floodlight
- Pan and tilt light aiming adjustment
- IP55 weatherproof rating
- Optional wall mount spacer available: 907-0-988

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to +45°C
Ingress Protection Rating	IP55
Wattage	20
Beam Angle	90° x 90° (Per Head)
Pan & Tilt Adjustment	Pan Left 40°, Pan Right 40° (Without Spacer). Pan Left 45°, Pan Right 45° (With Spacer)
Energy Efficiency	Class G
Energy Usage	20KwH/1000H

Data sheet

LED200FLBE

Light / LED Lighting

Lumen output (lm)	1680
Colour Temperature (K)	4000
LED Type	SMD (Intergrated)
Mounting Hole Centres (mm)	60
Multiple Unit Support	Yes
Cable Entry(s)	Bottom Entry (Knockouts), Back Entry

General

Weight (g)	441
Height (mm)	160
Width (mm)	167
Depth (mm)	50
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Fittings, Setting Knob
Accessories (Optional)	Corner mount bracket (907.0.756), Wall spacer (907.0.971)
EAN Number	5012483014127
Guarantee Period	3 Years

Data sheet

LED200FLBE

Light / LED Lighting

Line Diagrams

