



Plug in connector between the terminal block and the LED array




Photo cell version shown



### LED ECONOMY BULKHEADS

- Polycarbonate construction: impact and corrosion resistant
- BESA box mounting
- Pre-formed 20mm cable entry knockouts: easy wiring access
- Plug in connector between the terminal block and the LED array. Terminal block is located on the base, allowing for easy wiring and the LED array can be removed during installation
- 5 year warranty

### PHOTOCELL VERSION:

- Integral photocell: automatic dusk to dawn operation (on/off at 30/80 lux)

• M.O.M: 1 / O.P.Q: 12

Code	Version	Colour	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP Rating
VECOBHLED	Standard	Black	12W	3000K	900 lm	20,000 hrs	IP65
VECOBHLPC	Photocell						



20mm cable entry knockouts

LED LAMP SPECIFICATIONS:	
Luminaire lumens (with diffuser)	<b>900 lm</b>
Lumens from chip (no diffuser)	<b>1200 lm</b>
Useful lumens	<b>850 lm</b>
Rated Wattage	12W
Rated luminous flux	850 lm
Nominal life time of the lamp	20,000 hrs
Colour temperature	3000K
Number of switching cycles before premature lamp failure	10,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
Nominal beam angle	120°
Rated power	12W
Rated lamp lifetime	20,000 hrs
Lamp power factor	>0.65
Lumen maintenance factor at end of nominal life	70%
Starting time	<0.1
Colour rendering	80
Colour consistency	Within a six step Macadam ellipse
Rated beam angle	120°
Voltage / Frequency	240V~50Hz
Not suitable for accent lighting	