



Fuse-link, LV, 20 A, AC 550 V, BS88/F1, 14 x 59 mm, gL/gG, BS

Part no. 20AMP 550V AC BS88 FUSE
Catalog No. NSD20

Delivery program

| | | | |
|------------------------------|---|----|---------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 20 |
| Rated voltage | | | AC 550 V |
| Construction size | | | BS88/F1 |
| Size | | | 14 x 59 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 80 |
| usable for size/applications | | | general industrial applications |
| Standard/Approval | | | BS |
| Shape | | | offset bladed tags |
| Standards/Regulations | | | BS88-2 IEC 60269-2 |
| Optional accessories | | | fuse-holder 32NNS and SC32 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 20 |
| Rated voltage | | V | 550 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 80 |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator | | | None |
| Insulated metal gripping lugs (IMGL) | | | No |