Xnightsbridge


DATASHEET



VFRIC8WW

230V IP65 8W Fire-Rated Valknight LED Downlight

www.mlaccessories.co.uk



| MLA PART CODE | VFRIC8WW |
|--------------------------|--|
| DESCRIPTION | 230V IP65 8W Fire-Rated Valknight LED Downlight 3000K |
| NET WEIGHT (KG) | 0.272 |
| DIFFUSER | Clear |
| DIMENSIONS (MM) | Diameter - 80 Projection - 4 Recessed Depth - 50 Recessed Depth with IC Cage - 90 Minimum Void - 100 |
| CUT-OUT (MM) | Cut-out Diameter - 65 |
| CONSTRUCTION | Construction - Die-cast aluminium |
| CLASS | II |
| IP RATING | IP65 (IP20 from above) |
| WATTAGE (W) | 8 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 580 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 68.46 |
| CIRCUIT WATTAGE (W) | 8.497 |
| ССТ | 3000K |
| LIGHT COLOUR | Warm White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.04111 |
| BEAM ANGLE (DEGREES) | 40 |
| LIFE SPAN (HRS) | 25,000 |
| DIMMABLE | Yes* |
| EMERGENCY CONVERSION KIT | VFR7EM |
| FIRE-RATED | Tested to 30/60/90 minutes |





Xnightsbridge

| I-JOIST RATED | 30 minutes |
|--|---|
| IC RATED | With IC cage only |
| INPUT VOLTAGE | 230V 50Hz |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 8W OUTPUT VOLTAGE - 25-36V OUTPUT CURRENT - 240mA POWER FACTOR - >0.9 AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 85°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055832943334 |

Date Created: 25/04/2022 08:01





