


DATASHEET



TRLED24EM

230V IP65 4ft 41W Twin LED Non-Corrosive Emergency

www.mlaccessories.co.uk



MLA PART CODE	TRLED24EM
DESCRIPTION	230V IP65 4ft 41W Twin LED Non-Corrosive Emergency
NET WEIGHT (KG)	2.75
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1263 Height - 90 Width - 129
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	41
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	4670
LUMENS LIGHT SOURCE ONLY (LM)	5600
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	141.38
LUMENS EMERGENCY MODE (LM)	795
CIRCUIT WATTAGE (W)	39.63
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
RUNNING CURRENT (A)	0.180
DISPLACEMENT FACTOR	>0.9
SVM	0.76
PST-LM	0.034
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000

DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 47W EFFICIENCY FULL LOAD - 90.12% ISOLATION - SELV
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832971122

Date Created: 04/04/2022 15:30

