TRT030N

Electronic Room Thermostat

Features & Benefits

- Easily adjustable dial with clearly marked temperature scale
- 5°C to 30°C set temperature range
- Temperature swing adjustment (using DIP switches) between a 0.5°C and 1°C
- PID control
- Output LED (illuminates on call for heat)
- Switch Type: Single pole, single throw (SPST)
- Surface mount with wall plate included



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Connection	3 Wire
Setting Type	Dial
Set Temperature Range	5°C to 30°C, User Adjustable
ErP Product Class	Class 1
Boiler Type	3CYC (Gas) or 6CYC (Oil) Dip Switch Adjustable



Data sheet **TRT030N**

Climate / Programastat Plus

Temperature Swing (Hysteresis)	1°C or 0.5°C
PID Control	Supported (ON/OFF Switchable)
Switch type	Single Pole, Single Throw (SPST)
Mounting Hole Centres (mm)	60
Standby Consumption	<4W
Switch rating	6A Resistive, 2A Inductive
Cable Entry(s)	Back Entry

General

Weight (g)	132.7
Height (mm)	86
Width (mm)	88
Depth (mm)	38
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Rawl Plugs, Screws
EAN Number	5012483014356
Guarantee Period	3 Years



Line Diagrams



