### Data sheet TRT031N

#### Climate / Programastat Plus

### TRT031N

## Electronic Frost Thermostat with Tamper Proof Cover

#### **Features & Benefits**

- Easily adjustable dial with clearly marked temperature scale
- Frost protection against the risk of freezing pipes
- 5°C to 10°C set temperature range
- Tamper proof cover protects thermostat settings
- Temperature swing adjustment (using DIP switches) between a 0.5 °C and 1°C
- PID control

**Technical Data** 

- Switch Type: Single pole, single throw (SPST)
- · Surface mount with wall plate included



Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Connection	3 Wire
Setting Type	Dial
Set Temperature Range	5°C to 10°C, User Adjustable
ErP Product Class	Class 1



A **theben** Group Company

Subject to technical changes and misprints

additional information at: https://www.timeguard.com

This data was generated on

17/05/2022

Boiler Type	3CYC (Gas) or 6CYC (Oil) Dip Switch Adjustable
Temperature Swing (Hysteresis)	1°C or 0.5°C
PID Control	Supported (ON/OFF Switchable)
Switch type	Single Pole, Single Throw (SPST)
Mounting Hole Centres (mm)	60
Standby Consumption	<4W
Switch rating	6A Resistive, 2A Inductive
Cable Entry(s)	Back Entry

#### General

Weight (g)	160
Height (mm)	86
Width (mm)	88
Depth (mm)	38
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Rawl Plugs, Screws, Tamperproof Cover
EAN Number	5012483014370
Guarantee Period	3 Years



A **theben** Group Company

Subject to technical changes and misprints

additional information at: https://www.timeguard.com


This data was generated on

17/05/2022

# Data sheet **TRT031N**

#### Climate / Programastat Plus

#### Line Diagrams





Subject to technical changes and misprints

additional information at: https://www.timeguard.com

This data was generated on