

TRT034N

7 Day Digital Programmer – 1 Channel



Features & Benefits

- 7 day programming for use with room thermostat
- 3 timed control periods per day (5 day and 2 or 7 day programming).
- Programme copy function
- 1 and 2 and 3 hour boost function
- Holiday mode
- Always ON and OFF override mode
- Blue LED screen illuminates upon setting
- Automatic summer and winter changeover
- Change over contacts
- Factory fitted rechargeable battery backup

Technical Data

| | |
|------------------------------|------------------------|
| Operating Voltage | 230V AC |
| Frequency | 50Hz |
| Installation Type | Surface |
| Earth Class Rating | Class II |
| Operating Temperature | 0°C to 40°C |
| Connection | 3 Wire |
| Setting Type | Digital |
| Battery Type | 3.6V 20mA Rechargeable |
| Power Reserve | 1 Week (7 Days) |

Data sheet

TRT034N

Climate / Programastat Plus

| | |
|-----------------------------------|--|
| Program Modes | 24 Hour/7 Day, Holiday Mode, 1,2 or 3 Hour Boost |
| Switch type | Single Pole, Double Throw (SPDT) |
| Mounting Hole Centres (mm) | 60 |
| Standby Consumption | <8W |
| Switch rating | 3A Resistive, 1A Inductive |
| Shortest Switching Time | 1 Minute |
| Programmable Slots | 3 ON, 3 OFF |
| Cable Entry(s) | Back Entry |

General

| | |
|-------------------------------|--------------------|
| Weight (g) | 194.2 |
| Height (mm) | 90 |
| Width (mm) | 135 |
| Depth (mm) | 30 |
| Body Construction | Polycarbonate |
| Product Colour | White |
| Accessories (Included) | Rawl Plugs, Screws |
| EAN Number | 5012483014400 |
| Guarantee Period | 3 Years |

Line Diagrams

