

PDFMMINIL

360° Flush Mount Linkable Mini PIR Sensor



Features & Benefits

- Designed For Corridor and Multi-Zone Use
- Mini unobtrusive design
- 360° Detection
- Twist & Lock Design For Easy Access
- Up To 5 Slaves Can Be Added To 1 Master.
Pre-Wired RJ11 Plug-in Slave Units For Quick Installation
- LUX Adjustment
- Time Adjustment For Slave Units Set Via Master Only
- Termination Box For Ease Of Wiring
- Masking Kit Included
- LED movement indicator

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Mount
Earth Class Rating	Class II (Power Box), Class III (PIRs)
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP40
Setting Type	Dial
Max Mounting Height (Mtr)	2.5

Data sheet

PDFMMINIL

Light / PIR Presence Detectors

Presence Detection (Mtr)	3
Motion Detection (Mtr)	8
Detection Angle	360°
Hole Cut-Out Size (mm)	40
Standby Consumption	<0.5W
Number of Channels	1
Switch rating	250W LED/CFL/Fluorescent, 2300W Halogen
ON Time Adjustment	30 Sec, 2m, 5m, 10m, 15m, 30m. User Adjustable
Lux Level	10 to 2000
Detection Range (Mtr)	8
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Yes PDFMMINILS (Slave PIRs)
Cable Entry(s)	Side Entry (Power Box)

General

Weight (g)	140
Height (mm)	PIR 47, Power Box 35
Width (mm)	PIR 47, Power Box 175
Depth (mm)	PIR 64, Power Box 35
Body Construction	Polycarbonate
Product Colour	White
Accessories (Optional)	PDFMINILS (Slave PIR)
EAN Number	5012483014011

Guarantee Period

3 Years

Line Diagrams

