

PDFMMINILS

360° Flush Mount Linkable Mini PIR Slave Sensor

Features & Benefits

- Designed For Corridor and Multi-Zone Use
- Mini unobtrusive design
- Up to 5 Plug & Play slave units can be added
- Imitates the settings of the master PIR (PDFMMINIL)
- Pre-installed 5 Mtr Lead



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Mount
Earth Class Rating	Class II (Power Box), Class III (PIRs)
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP40
Setting Type	Dial
Max Mounting Height (Mtr)	2.5
Presence Detection (Mtr)	3
Motion Detection (Mtr)	8
Detection Angle	360°
Hole Cut-Out Size (mm)	40

Data sheet

PDFMMINILS

Light / PIR Presence Detectors

Standby Consumption	<0.5W
Number of Channels	1
Switch rating	250W LED/CFL/Fluorescent, 2300W Halogen
ON Time Adjustment	30 Sec, 2m, 5m, 10m, 15m, 30m. User Adjustable
Lux Level	10 to 2000
Detection Range (Mtr)	8
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Yes PDFMMINILS (Slave PIRs)
Cable Entry(s)	RJ45 Loop Connection (PIR)

General

Weight (g)	104
Height (mm)	47
Width (mm)	47
Depth (mm)	64
Body Construction	Polycarbonate
Product Colour	White
Accessories (Optional)	PDFMINILS (Slave PIR)
EAN Number	5012483014028
Guarantee Period	3 Years

Line Diagrams

